


Cisco CCIE/CCNP Certification 350-601 DCCOR Exam



- **Vendor: Cisco**
- **Exam Code: 350-601**
- **Exam Name: Implementing and Operating
Cisco Data Center Core Technologies (DCCOR)**

Get Complete Version Exam 350-601 Dumps with VCE and PDF Here



<https://www.passleader.com/350-601.html>

NEW QUESTION 1

Which virtual MAC address is the default for HSRP version 2 group 10?

- A. 0000.5E00.0110
- B. 0000.0C9F.F00A
- C. 3716.1350.1C0A
- D. 0000.0C9F.F010

Answer: B

Explanation:

HSRP version 2 permits an expanded group number range, 0 to 4095, and consequently uses a new MAC address range 0000.0C9F.F000 to 0000.0C9F.FFFF.

https://www.cisco.com/c/en/us/td/docs/ios-xml/ios/ipapp_fhrp/configuration/xr-3s/fhrp-xr-3s-book/fhrp-hsrp-v2.html

NEW QUESTION 2

Which mroute state is created when Bidirectional PIM is deployed at a site?

- A. *.G
- B. MVPN Type-6
- C. MVPN Type-7
- D. S.G

Answer: A

NEW QUESTION 3

A small remote office is set to connect to the regional hub site via NSSA ASBR. Which type of LSA is sent to the remote office OSPF area?

- A. type 7 LSA
- B. type 1 LSA
- C. type 5 LSA
- D. type 3 LSA

Answer: A

Explanation:

<https://www.cisco.com/c/en/us/support/docs/ip/open-shortest-path-first-ospf/6208-nssa.html>

NEW QUESTION 4

The engineer must configure SPAN on a Cisco Nexus 5000 Series Switch to get a capture of the traffic from these applications for an in-depth packet analysis. Which two SPAN characteristics must be considered? (Choose two.)

- A. SPAN source ports can be monitored in multiple SPAN sessions.
- B. The Ethernet, FC, vFC, port channel, SAN port channel can be used as SPAN source ports.
- C. A SPAN source port cannot be a destination SPAN port.
- D. Only Ethernet, FC, vFC, port channel port types can be used as SPAN source ports.
- E. The rx/tx option is available for VLAN or VSAN SPAN sessions.

Answer: BC

NEW QUESTION 5

A customer has a requirement to deploy a cloud service and needs to have full control over the underlying OS, data and applications. Which cloud model meets this requirement?

- A. MaaS
- B. PaaS
- C. SaaS
- D. IaaS

Answer: D

Explanation:

<https://www.zdnet.com/article/cloudy-concepts-iaas-paas-saas-maas-caas-xaas/>

<https://rubygarage.org/blog/iaas-vs-paas-vs-saas>

NEW QUESTION 6

Due to a major version change, an engineer must perform a software upgrade on a Cisco Nexus Series switch. Which two technologies can be implemented to reduce disruptions to the network during the upgrade? (Choose two.)

- A. vPC
- B. HSRP
- C. VDC
- D. MLAG
- E. PAgP

Answer: AC

NEW QUESTION 7

What are two capabilities of the Cisco Network Assurance Engine? (Choose two.)

- A. It validates that devices comply with network security policies.
- B. It predicts the impact of changes to the network.
- C. It predicts the network load on a data center.
- D. It ensures that network performance meets an SLA.
- E. It verifies the speed of network packet flows by using telemetry.

Answer: AB

Explanation:

<https://www.cisco.com/c/en/us/products/data-center-analytics/network-assurance-engine/index.html>

NEW QUESTION 8

A server engineer wants to control power usage on a Cisco UCS C-Series rack server down to the component level. Which two components support specific power limits? (Choose two.)

- A. storage controller
- B. network controller
- C. processor
- D. graphic card
- E. memory

Answer: AB

NEW QUESTION 9

An engineer wants to create a backup of Cisco UCS Manager for disaster recovery purposes. What are two characteristics of a full state backup of a Cisco UCS Manager database? (Choose two.)

- A. contains all of the runtime states and statuses but not the configurations
- B. performs a complete binary dump of the database as a .bin file

- C. performs a complete binary dump of the database as a .sql file
- D. performs a complete binary dump of the database as a .txz file
- E. contains all of the configurations

Answer: BE

NEW QUESTION 10

An engineer is asked to use SaaS to manage Cisco computing. Which two items are needed to accomplish the task? (Choose two.)

- A. Intersight
- B. UCS Central
- C. Device/Claim ID
- D. Node name/Serial Number
- E. UCS Manager

Answer: AE

NEW QUESTION 11

Which two settings must be configured before enabling a Cisco UCS Manager domain for Cisco Intersight connectivity? (Choose two.)

- A. SMTP servers
- B. SMTP reply-to address
- C. NTP servers
- D. Syslog redirection
- E. DNS servers

Answer: CE

NEW QUESTION 12

Where is the witness deployed in a two-node Cisco HyperFlex Edge deployment?

- A. to the HyperFlex Edge two-node cluster
- B. to Cisco Intersight
- C. to a third-party cloud provider
- D. to an additional server with network access to HyperFlex Edge

Answer: B

NEW QUESTION 13

Which two hypervisors does Cisco HyperFlex support? (Choose two.)

- A. OpenStack
- B. Citrix XenServer
- C. VMware vSphere
- D. RedHat KVM
- E. Microsoft Hyper-V

Answer: CE

Explanation:

The platform supports multiple hypervisors and virtualized environments (Microsoft Windows Server 2019 Hyper-V, VMware vSphere), Docker containers with Kubernetes, multicloud services, and edge deployments to efficiently and economically deploy, monitor, and manage applications. <https://www.cisco.com/c/dam/en/us/products/se/2017/2/Collateral/le-56101-aag.pdf>

NEW QUESTION 14

Which two statements about the process of performing an EPLD upgrade on a Cisco MDS 9000 Series Switch are true? (Choose two.)

- A. The upgrade can be performed from the standby supervisor module.
- B. The upgrade process disrupts only the module that is being upgraded.
- C. The active supervisor can be upgraded.
- D. If an upgrade is interrupted, the upgrade continues after a connection is restored.
- E. Modules must be online to be upgraded.

Answer: AB

Explanation:

https://www.cisco.com/c/en/us/td/docs/switches/datacenter/mds9000/sw/8_x/release_notes/epld/epld_rn_8x.html

NEW QUESTION 15

What is an advantage of NFS as compared to Fibre Channel?

- A. NFS removes the impact of IP overhead.
- B. NFS enables thin provisioning for LUNs.
- C. NFS provides direct access to the underlying storage hardware.
- D. NFS provides the dynamic allocation of storage capacity.

Answer: B

NEW QUESTION 16

An engineer must ensure fabric redundancy when implementing NPV mode on a Cisco MDS 9000 Series Switch. Which action enables fabric redundancy?

- A. Use TE ports to connect to upstream switches.
- B. Add a port channel to upstream switches.
- C. Configure the NPV devices to use an external FLOGI database.
- D. Connect the NPV devices to multiple upstream switches.

Answer: B

Explanation:

https://www.cisco.com/c/en/us/td/docs/switches/datacenter/mds9000/sw/5_0/configuration/guides/int/nxos/cli_interfaces/pc.html

NEW QUESTION 17

Which two methods are available to manage an ACI REST API session authentication when a user is unauthenticated? (Choose two.)

- A. POST to aaaUserLogin
- B. GET to aaaListDomains
- C. GET aaaRefresh
- D. DELETE to aaaLogout
- E. POST to aaaLogin

Answer: CE

NEW QUESTION 18

A POAP-enabled Cisco Nexus switch will not enter POAP mode. Which two conditions should be verified? (Choose two.)

- A. No startup configuration is available.
- B. The switch is in bootup process.
- C. The license file is missing on the switch.
- D. Bootflash must contain a special directory named POAP with poap.py file.
- E. No Cisco NX-OS image is present on the bootflash.

Answer: AB

NEW QUESTION 19

A network architect is asked to design and manage geographically distributed data centers across cities and decides to use a Multi-Site Orchestrator deployment. How many orchestrators should be deployed?

- A. 5
- B. 3
- C. 4
- D. 2

Answer: B

NEW QUESTION 20

An engineer must configure RBAC in Cisco UCS Manager in an existing data center environment. Which two roles can be used to configure LAN connectivity policies? (Choose two.)

- A. server-profile
- B. network-admin
- C. operations
- D. enable
- E. admin

Answer: BE

NEW QUESTION 21

.....

Get Complete Version Exam 350-601 Dumps with VCE and PDF Here



<https://www.passleader.com/350-601.html>